

Dive Stand, One Meter Rear Cheyenne, product number 22121

The dive stand shall be designed for use with in-ground swimming pools conforming to World Swimming standards for diving portions of Class B and C swimming pools.

The dive stand shall consist of the following components:

Superstructure

The superstructure shall consist of a pedestal, side guardrails, fulcrum supports, sloping access ladder, adjustable fulcrum, and hinged rear board support. The pedestal shall be a column 8" x 8" x 3/16" wall thickness. It shall be set at a 15 degree angle toward pool edge, include a 1/4" top plate and 1/2" bottom plate, and be T.I.G. welded with 3/16" reinforcing gussets.

The side guardrails shall be constructed of 1.90" x .065" wall thickness. Fulcrum support tubes shall be 1.90" x .145" wall thickness, sloping access ladder is to be 1.90" x .109" wall thickness. 304L Standard material, 316L optional upgrade available.

The adjustable fulcrum shall be operable using a single hand or foot. The axle shall be covered with a stainless steel lined rubber sleeve and be fitted with stainless steel spur gears at each end meshing onto stainless steel gear racks. All gears shall be covered and there shall be visible markings for positioning the axle.

Two hinged rear board supports shall be provided. They shall facilitate full range of motion, allowing the board (by others) to be rendered inoperable when not in use.

Steps

Two (2) 15-degree step treads shall be provided. They shall be 26" wide, have an integral non-slip top surface, and shall be injection molded using U.V. stabilized ABS plastic.





Anchor Kit (1M Rear Access) - PN 22140-00 (SOLD SEPARATELY)

The dive stand shall be supported by an anchor kit which includes the following:
One (1) 16" x 16" 304L series stainless steel pedestal cage anchor
Two (2) heavy-duty 4" fabricated stainless flange type anchors
Flange mount options available for retrofit applications.

Warranty

Spectrum Standard

BOARD	DIM "A"
16' MAXIFLEX	5'-3 11/16"
16' DURAFLEX	5'-8 3/4"
16' SR SMITH	6'-4 5/8"
14' DURAFLEX	4'-6"
14' SR SMITH	5'-4 5/8"
12' SR SMITH	4'-4 11/16"



7100 Spectrum Lane Missoula, Montana 59808
800.791.8056 www.spectrumaquatics.com

ENGINEERING DATA

PRODUCT:	DIVESTAND CHEYENNE 1M REAR ACCESS LADDER			
MODEL #:	22121-00	CATALOG #:	22121	REVISION: A
MATERIAL:				
FINISH #:				

NOTE:

⚠ DIMENSIONS VARY WITH SPECIFIC APPLICATIONS. SPECIFICATIONS ARE NOMINAL AND ARE SUBJECT TO CHANGE. PLEASE CONTACT SPECTRUM AQUATICS FOR CUSTOM APPLICATIONS