

# Ladder, 25" Standard 2 Step, product number 35129-25

The ladder shall be fabricated of 1.90" O.D. x .065", .109", or .145" wall thickness 304L stainless steel. Each rail shall have three bends that are to be wrinkle free. Provided with two (2) rubber bumpers.

### **Steps**

Two (2) step treads shall be provided. They shall be 19.66in wide x 5.00in deep, have a non-slip top surface, and shall be made of high density plastic. Hardware included.


#### **Anchors**

The ladder shall be supported by two (2) 4" bronze wedge anchors and two (2) stainless steel keyhole escutcheons.

(Not Included)

#### Warranty

Two year limited warranty.



## NOTE:

DIMENSIONS VARY WITH SPECIFIC APPLICATIONS. SPECIFICATIONS ARE NOMINAL AND ARE SUBJECT TO CHANGE. PLEASE CONTACT SPECTRUM AQUATICS FOR CUSTOM APPLICATIONS



A PAYCORE Company 7100 Spectrum Lane

Missoula, Montana 59808 800.791.8056

www.spęctrumaquatics.com

# ENGINEERING DATA

PRODUCT: 25in STANDARD 2 STEP - 1.9 -MODEL #: **LADDER** CATALOG #: 35129-25 REVISION: MATERIAL **304L STAINLESS STEEL BUFFED TO NEAR #6 FINISH OR 500 GRIT** FINISH #: