

Rails The ladder shall be fabricated of 1.90" O.D. x .065", .109", or .145" wall

thickness 304L stainless steel. Each rail shall have three bends that are to be wrinkle free. Provided with two (2) rubber bumpers.


Two (2) step treads shall be provided. They shall be 19.66in wide x 5.00in deep with a non-slip top surface, and shall be made of high density plastic. Hardware included.

Anchors

The ladder shall be supported by two (2) 4" bronze wedge anchors and two (2) stainless steel keyhole escutcheons. (Not Included)

Warranty

Two year limited warranty.



NOTE:

DIMENSIONS VARY WITH SPECIFIC APPLICATIONS. SPECIFICATIONS ARE NOMINAL AND ARE SUBJECT TO CHANGE. PLEASE CONTACT SPECTRUM AQUATICS FOR CUSTOM APPLICATIONS



A PAYCORE Company

7100 Spectrum Lane Missoula, Montana 59808 800.791.8056

www.spectrumaquatics.com

ENGINEERING DATA

27in HEAVY DUTY 2 STEP - 1.9 -PRODUCT: MODEL #: **LADDER** CATALOG #: 36178-27 REVISION: MATERIAL **304L STAINLESS STEEL** FINISH #: **BUFFED TO NEAR #6 FINISH OR 500 GRIT**